

Datasheet

P3WB Series

Prosumer RAID Desktop Storage

Thunderbolt™ 3 Hardware RAID Storage for Creative Professionals

Benefits

- Create, edit, view, and share brilliant 3D and 4K video
- Seamlessly transfer terabytes of data in minutes rather than hours
- Safely backup massive creative projects
- · Simplify and accelerate your workflow

Highlights

- Supports maximum throughput allowed by Thunderbolt™ 3 interface
- Expand storage capacity and backup for workstations
- Supports simultaneous streaming, editing, and backup of 4K video
- Dual Thunderbolt™ ports for daisy-chaining


- Hot-swappable drive bays for effortless drive access and serviceability
- Portable hardware RAID protection for offsite shoots
- Massive storage capacity for backing up creative projects and digital libraries
- Essential to P3WB end-to-end 4K workflow environment

P3WB RAID Series

- The P3WB Series with Thunderbolt 3 technology delivers blistering performance for creative professionals creating high resolution video and rich media content.
- Built to maximize the available line rate of Thunderbolt 3, video creators, photographers, graphic artists, and engineers alike can transfer and display 4K video files simultaneously at lightning speeds.
- P3WB is the world's first RAID 5 solution featuring Thunderbolt 3 technology, enabling pros and enthusiasts to create, edit, and view live 4K video streams while simultaneously backing up files to the system.

P3WB and Workstations

- P3WB is the storage launched for workstations that have Thunderbolt 3 ports.
 Available in 4-bay and 8-bay configurations.
- Storage capacity for massive 4K projects can be expanded by daisy-chaining multiple P3WB systems.



P3WB Series Specifications

Model	P3WBX4 White Box (Diskless)	P3WBX8 White Box (Diskless)
General Information		
Form Factor	4-Bay hardware RAID enclosure	8-Bay hardware RAID enclosure
Drive Support	3.5" SATA 6Gb/s (user needs to buy the extra 2.5" to 3.5" HDD bracket for the AVL 2.5" HDD/SSD)	3.5" SATA 6Gb/s (user needs to buy the extra 2.5" to 3.5" HDD bracket for the AVL 2.5" HDD/SSD)
Processor	Integrated SAS ROC (Raid-On-Chip)	Integrated SAS ROC (Raid-On-Chip)
Memory	1GB DDR3 1866 ECC on board	1GB DDR3 1866 ECC on board
Controller (TBT chip)	Intel Titan Ridge	Intel Titan Ridge
Expansion	2 Thunderbolt ports use for daisy chain	2x Thunderbolt ports use for daisy chain
Camera Range	N/A	N/A
(optional)		
Host Interface*	2x USB-C ports either Thunderbolt3 40Gbps (power the host up to 85W - Port A only) or USB 3.2 Gen 2	2x USB-C ports either Thunderbolt3 40Gbps (power the host up to 85W - Port A only) or USB 3.2 Gen 2
Thunderbolt Port	Dual Thunderbolt ports, one for host connection, one for downstream daisy chain	Dual Thunderbolt ports, one for host connection, one for downstream daisy chain
Port type	USB Type C	USB Type C
PCI Express Port	NA	NA NA
Graphic Port	NA .	NA NA
Microphone	NA	NA NA
RAID & Features	IVA	IVA
I KAILLI AVAL	I RAID O 1 5 6 10 IROD	RAID 0 1 5 6 10 50 60 IROD
RAID Level	RAID 0, 1, 5, 6, 10, JBOD	RAID 0, 1, 5, 6, 10, 50, 60, JBOD
Hot Spare	Yes	Yes
Hot Spare Max LUNs	Yes 128	Yes 128
Hot Spare Max LUNs Hot Swap	Yes	Yes
Hot Spare Max LUNs Hot Swap Software Highlights	Yes 128 Yes	Yes 128 Yes
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only)	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only)
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features Physical Inforamtion	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features Physical Inforamtion Dimension	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 191 x 123 x 277 (H x W x D, mm)	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 309 x 123 x 277 (H x W x D, mm)
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features Physical Inforamtion Dimension Weight	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 309 x 123 x 277 (H x W x D, mm) 5.9kg
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features Physical Inforamtion Dimension	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 191 x 123 x 277 (H x W x D, mm) 4.2kg	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 309 x 123 x 277 (H x W x D, mm)
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features Physical Inforamtion Dimension Weight AC Input	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 191 x 123 x 277 (H x W x D, mm) 4.2kg 100-240V auto-ranging, 50~60Hz AC	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 309 x 123 x 277 (H x W x D, mm) 5.9kg 100-240V auto-ranging, 50~60Hz AC
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features Physical Inforamtion Dimension Weight AC Input Power Supply	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 191 x 123 x 277 (H x W x D, mm) 4.2kg 100-240V auto-ranging, 50~60Hz AC	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 309 x 123 x 277 (H x W x D, mm) 5.9kg 100-240V auto-ranging, 50~60Hz AC 250W PSU
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features Physical Inforamtion Dimension Weight AC Input Power Supply Environment	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 191 x 123 x 277 (H x W x D, mm) 4.2kg 100-240V auto-ranging, 50~60Hz AC 250W PSU	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 309 x 123 x 277 (H x W x D, mm) 5.9kg 100-240V auto-ranging, 50~60Hz AC
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features Physical Inforamtion Dimension Weight AC Input Power Supply Environment Temperature Range Humidity	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 191 x 123 x 277 (H x W x D, mm) 4.2kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C , Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing , Storage: 5% - 95% non-condensing	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 309 x 123 x 277 (H x W x D, mm) 5.9kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C , Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing , Storage: 5% - 95% non-condensing
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features Physical Inforamtion Dimension Weight AC Input Power Supply Environment Temperature Range	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 191 x 123 x 277 (H x W x D, mm) 4.2kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C , Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing , Storage: 5% - 95%	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 309 x 123 x 277 (H x W x D, mm) 5.9kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C , Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing , Storage: 5% - 95%
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features Physical Inforamtion Dimension Weight AC Input Power Supply Environment Temperature Range Humidity Regulatory/Safety Green Certificate	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 191 x 123 x 277 (H x W x D, mm) 4.2kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C , Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing , Storage: 5% - 95% non-condensing NA (EMC: FCC, CE , Safety: cTUVus, CB by the customer request)	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 309 x 123 x 277 (H x W x D, mm) 5.9kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C , Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing , Storage: 5% - 95% non-condensing NA (EMC: FCC, CE , Safety: cTUVus, CB by the customer request)
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features Physical Inforamtion Dimension Weight AC Input Power Supply Environment Temperature Range Humidity Regulatory/Safety Green Certificate Warranty and Support	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 191 x 123 x 277 (H x W x D, mm) 4.2kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C , Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing , Storage: 5% - 95% non-condensing NA (EMC: FCC, CE , Safety: cTUVus, CB by the customer request) ROHS, WEEE	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 309 x 123 x 277 (H x W x D, mm) 5.9kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C , Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing , Storage: 5% - 95% non-condensing NA (EMC: FCC, CE , Safety: cTUVus, CB by the customer request) ROHS, WEEE
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features Physical Inforamtion Dimension Weight AC Input Power Supply Environment Temperature Range Humidity Regulatory/Safety Green Certificate Warranty and Support	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 191 x 123 x 277 (H x W x D, mm) 4.2kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C , Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing , Storage: 5% - 95% non-condensing NA (EMC: FCC, CE , Safety: cTUVus, CB by the customer request)	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 309 x 123 x 277 (H x W x D, mm) 5.9kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C , Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing , Storage: 5% - 95% non-condensing NA (EMC: FCC, CE , Safety: cTUVus, CB by the customer request)
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features Physical Inforamtion Dimension Weight AC Input Power Supply Environment Temperature Range Humidity Regulatory/Safety Green Certificate Warranty and Support Warranty Support	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 191 x 123 x 277 (H x W x D, mm) 4.2kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C, Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing, Storage: 5% - 95% non-condensing NA (EMC: FCC, CE, Safety: cTUVus, CB by the customer request) ROHS, WEEE	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 309 x 123 x 277 (H x W x D, mm) 5.9kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C , Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing , Storage: 5% - 95% non-condensing NA (EMC: FCC, CE , Safety: cTUVus, CB by the customer request) ROHS, WEEE
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features Physical Inforamtion Dimension Weight AC Input Power Supply Environment Temperature Range Humidity Regulatory/Safety Green Certificate Warranty and Support Warranty Support Packing Material Thunderbolt3 / USB	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 191 x 123 x 277 (H x W x D, mm) 4.2kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C, Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing, Storage: 5% - 95% non-condensing NA (EMC: FCC, CE, Safety: cTUVus, CB by the customer request) ROHS, WEEE	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 309 x 123 x 277 (H x W x D, mm) 5.9kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C , Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing , Storage: 5% - 95% non-condensing NA (EMC: FCC, CE , Safety: cTUVus, CB by the customer request) ROHS, WEEE
Hot Spare Max LUNs Hot Swap Software Highlights Supported OS Management Tool Ecosystem Integration Product Specific Features NAS Features Physical Inforamtion Dimension Weight AC Input Power Supply Environment Temperature Range Humidity Regulatory/Safety Green Certificate Warranty and Support Warranty Support Packing Material	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 191 x 123 x 277 (H x W x D, mm) 4.2kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C , Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing , Storage: 5% - 95% non-condensing NA (EMC: FCC, CE , Safety: cTUVus, CB by the customer request) ROHS, WEEE	Yes 128 Yes macOS/Windows, Driver and Management Tool. Linux (driver only) P3WB Utility NA Intelligent Cooling/Acoustic control, Drive SMART health Polling NA 309 x 123 x 277 (H x W x D, mm) 5.9kg 100-240V auto-ranging, 50~60Hz AC 250W PSU Operating: 5° ~ 35° C, Non-operating: -40° ~ 70° C Operating: 10% ~ 95% non-condensing, Storage: 5% - 95% non-condensing NA (EMC: FCC, CE, Safety: cTUVus, CB by the customer request) ROHS, WEEE 3-years standard warranty NA